ANCHEE



info@xingyuan-frdept.com

PASSENGER CAR,SUV AND LIGHT TRUCK
BROCHURE

PATTERN SUMMARY

HP



AC708



AC 808



AC 218

LT



AC 838



AC 858



AC 898

UHP



AC 818



AC718



GRANDTRAC MT1

SUV



AC 828

WINTER—TYRE



AC 868



arctic w-8



ARCTIC W-9

RUN—FLAT



TITAN ACF01

EV



EPFOUNDER CE101



ARCTIC W-6

ANCHEE



ANCHEE

PASSENGER



AC 808

TIRE SIZE	LOAD INDEX/ SPEED SYMBOL	STD. RIM (inch)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD (KG)	MAX LOAD (lbs)	MAX PRESSURE (KPa)	MAX PRESSURE (PSI)	UTQG
13 inch									
155/65R13	73S	4.50B	157	532	365	805	300	44	420 A A
155/65R13	73T	4.50B	157	532	365	805	300	44	420 A A
155/70R13	75T	4.50B	157	548	387	853	300	44	420 A A
155/80R13	79T	4.50B	157	578	437	963	300	44	420 A A
165/65R13	77T	5.00B	170	544	412	908	300	44	420 A A
165/70R13	79T	5.00B	170	562	437	963	300	44	420 A A
165/80R13	83T	4.50B	165	594	487	1074	300	44	420 A A
175/60R13	77H	5.00B	177	540	412	908	300	44	420 A A
175/70R13	82T	5.00B	177	576	475	1047	300	44	420 A A
185/70R13	86T	5.50B	189	590	530	1168	300	44	420 A A
14 inch									
155/65R14	75S	4½J	157	558	387	853	300	44	420 A A
155/65R14	75T	4½J	157	558	387	853	300	44	420 A A
165/60R14	75H	5J	170	554	387	853	300	44	420 A A
165/65R14	79T	5J	170	570	437	963	300	44	420 A A
165/70R14	81T	5J	170	588	462	1019	300	44	420 A A
NEW 175/60R14	79H	5J	177	566	437	963	300	44	420 A A
175/65R14	82H	5J	177	584	475	1047	300	44	420 A A
175/65R14	82T	5J	177	584	475	1047	300	44	420 A A
175/65R14	86T XL	5J	177	584	530	1168	340	50	420 A A
175/70R14	84T	5J	177	602	500	1102	300	44	420 A A
175/70R14	88T XL	5J	177	602	560	1235	340	50	420 A A
185/55R14	80H	6J	194	560	450	992	300	44	420 A A
185/60R14	82H	5½J	189	578	475	1047	300	44	420 A A
185/65R14	86H	5½J	189	596	530	1168	300	44	420 A A
185/70R14	88T	5½J	189	616	560	1235	300	44	420 A A
185/70R14	88H	5½J	189	616	560	1235	300	44	420 A A
195/60R14	86H	6J	201	590	530	1168	300	44	420 A A
195/70R14	91T	6J	201	630	615	1356	300	44	420 A A
195/70R14	91H	6J	201	630	615	1356	300	44	420 A A
205/60R14	88H	6J	209	602	560	1235	300	44	420 A A
205/70R14	98T XL	6J	209	644	750	1653	340	50	420 A A
205/75R14 (WSW)	95H	5½J	203	664	690	1521	300	44	420 A A
15 inch									
NEW 165/65R15	81H	5J	170	595	462	1019	300	44	420 A A
NEW 175/60R15	81H	5J	177	591	462	1019	300	44	420 A A
175/65R15	84H	5J	177	609	500	1102	300	44	420 A A
185/55R15	82V	6J	194	585	475	1047	300	44	420 A A
185/60R15	84H	5½J	189	603	500	1102	300	44	420 A A
185/60R15	88H XL	5½J	189	603	560	1235	340	50	420 A A
185/65R15	88H	5½J	189	621	560	1235	300	44	420 A A
185/65R15	88T	5½J	189	621	560	1235	300	44	420 A A
185/65R15	92T XL	5½J	189	621	630	1389	340	50	420 A A
195/50R15	82V	6J	201	577	475	1047	300	44	420 A A
195/55R15	85V	6J	201	595	515	1135	300	44	420 A A

TIRE SIZE	LOAD INDEX/ SPEED SYMBOL	STD. RIM (inch)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD (KG)	MAX LOAD (lbs)	MAX PRESSURE (KPa)	MAX PRESSURE (PSI)	UTQG
15 inch									
195/60R15	88H	6J	201	615	560	1235	300	44	420 A A
195/60R15	88V	6J	201	615	560	1235	300	44	420 A A
195/65R15	91H	6J	201	635	615	1356	300	44	420 A A
195/65R15	91V	6J	201	635	615	1356	300	44	420 A A
195/65R15	95H XL	6J	201	635	690	1521	340	50	420 A A
205/60R15	91H	6J	209	627	615	1356	300	44	420 A A
205/60R15	91V	6J	209	627	615	1356	300	44	420 A A
205/65R15	94H	6J	209	647	670	1477	300	44	420 A A
205/65R15	94V	6J	209	647	670	1477	300	44	420 A A
205/70R15	96T	6J	209	669	710	1565	300	44	420 A A
205/70R15 (WSW)	96T	6J	209	669	710	1565	300	44	420 A A
215/60R15	94H	6½J	221	639	670	1477	300	44	420 A A
215/65R15	96H	6½J	221	661	710	1565	300	44	420 A A
215/65R15	100HXL	6½J	221	661	800	1765	340	50	420 A A
215/70R15	98T	6½J	221	683	750	1653	300	44	420 A A
215/70R15 (WSW)	98T	6½J	221	683	750	1653	300	44	420 A A
16 inch									
NEW 185/55R16	83V	6J	194	610	487	1074	300	44	420 A A
195/50R16	88V XL	6J	201	602	560	1235	340	50	420 A A
195/55R16	87V	6J	201	620	545	1201	300	44	420 A A
195/55R16	91V XL	6J	201	620	615	1356	340	50	420 A A
195/55R16	91W XL	6J	201	620	615	1356	340	50	420 A A
195/60R16	89V	6J	201	640	580	1279	300	44	420 A A
205/50R16	87V	6½J	214	612	545	1201	300	44	420 A A
205/50R16	87W	6½J	214	612	545	1201	300	44	420 A A
205/50R16	91W XL	6½J	214	612	615	1356	340	50	420 A A
205/55R16	91V	6½J	214	632	615	1356	300	44	420 A A
205/55R16	91W	6½J	214	632	615	1356	300	44	420 A A
205/55R16	94V XL	6½J	214	632	670	1477	340	50	420 A A
205/55R16	94W XL	6½J	214	632	670	1477	340	50	420 A A
205/60R16	92H	6J	209	652	630	1389	300	44	420 A A
205/60R16	92V	6J	209	652	630	1389	300	44	420 A A
205/60R16	96H XL	6J	209	652	710	1565	340	50	420 A A
205/65R16	95H	6J	209	672	690	1521	300	44	420 A A
215/55R16	93V	7J	226	642	650	1433	300	44	420 A A
215/55R16	97V XL	7J	226	642	730	1609	340	50	420 A A
215/55R16	97W XL	7J	226	642	730	1609	340	50	420 A A
215/60R16	95H	6½J	221	664	690	1521	300	44	420 A A
215/60R16	99H XL	6½J	221	664	775	1709	340	50	420 A A
215/60R16	99V XL	6½J	221	664	775	1709	340	50	420 A A
225/55R16	99W XL	7J	233	654	775	1709	340	50	420 A A
225/60R16	98H	6½J	228	676	750	1653	300	44	420 A A



Technology used to reduce tyre noise.



Finely-divided tread pattern, corresponding to each division of the steel, ensures fantastic road grip performance in wet conditions and improves driving safety.



Four linear grooves ensures superior draining performance



Silicon formula optimizes tread stiffness, giving excellent wear and lowers rolling resistance.



Optimizing combination of tread construction, pattern and rubber effectively reduces fuel consumption.



The cut resistant tread reduces the possibility of irregular tread wear.



PASSENGER



AC 218

TIRE SIZE	LOAD INDEX/ SPEED SYMBOL	STD. RIM (inch)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD (KG)	(lbs)	MAX PRESSURE (KPa)	(PSI)	UTQG
16 inch									
205/55R16	94V XL	6½J	214	632	670	1477	340	50	420 A A



Multi-arc tread design provides superior manoeuvrability.



Technology used to reduce tyre noise.



Silicon formula improves road grip.



Decreased tread block rigidity efficiently reduces the noise between the tread and the road surface to increase driving comfort.



Big block pattern design improves tyre rigidity.



Four longitudinal grooves and wide draining design provide brilliant drainage performance and manoeuvrability.

TIRE SIZE	LOAD INDEX/ SPEED SYMBOL	STD. RIM (inch)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD (KG)	(lbs)	MAX PRESSURE (KPa)	(PSI)	UTQG
15 inch									
185/60R15	84H	5½J	189	603	500	1102	300	44	480 A A
185/60R15	88H XL	5½J	189	603	560	1235	340	50	480 A A
185/65R15	88H	5½J	189	621	560	1235	300	44	480 A A
185/65R15	88T	5½J	189	621	560	1235	300	44	480 A A
185/65R15	92T XL	5½J	189	621	630	1389	340	50	480 A A
195/55R15	85V	6J	201	595	515	1135	300	44	480 A A
195/60R15	88V	6J	201	615	560	1235	300	44	480 A A
195/60R15	88H	6J	201	615	560	1235	300	44	480 A A
195/65R15	91V	6J	201	635	615	1356	300	44	480 A A
195/65R15	91H	6J	201	635	615	1356	300	44	480 A A
195/65R15	95H XL	6J	201	635	690	1521	340	50	480 A A
205/65R15	94V	6J	209	647	670	1477	300	44	480 A A
205/65R15	94H	6J	209	647	670	1477	300	44	480 A A
16 inch									
NEW 195/55R16	87V	6J	201	620	545	1201	300	44	480 A A
NEW 195/60R16	89V	6J	201	640	580	1279	300	44	480 A A
205/55R16	91V	6½J	214	632	615	1356	300	44	480 A A
205/55R16	91W	6½J	214	632	615	1356	300	44	480 A A
205/55R16	94V XL	6½J	214	632	670	1477	340	50	480 A A
205/55R16	94W XL	6½J	214	632	670	1477	340	50	480 A A
205/60R16	92V	6J	209	652	630	1389	300	44	480 A A
205/60R16	92H	6J	209	652	630	1389	300	44	480 A A
205/60R16	96H XL	6J	209	652	710	1565	340	50	480 A A
215/55R16	93V	7J	226	642	650	1433	300	44	480 A A
215/55R16	97W XL	7J	226	642	730	1609	340	50	480 A A
215/55R16	97V XL	7J	226	642	730	1609	340	50	480 A A
215/60R16	95H	6½J	221	664	690	1521	300	44	480 A A
215/60R16	99V XL	6½J	221	664	775	1709	340	50	480 A A
215/60R16	99H XL	6½J	221	664	775	1709	340	50	480 A A



AC708



Handling Performance
Four wide circumferential grooves and and extra grooves in the blocks contribute to efficient drainage



Silence
Varied pitch design reduces noise and makes driving more fluid and comfortable

ANCHEE

RUN-FLAT



ANCHEE

ULTRA HIGH PERFOR MANCE



TITAN ACF01

	TIRE SIZE	LOAD INDEX/ SPEED SYMBOL	STD. RIM (inch)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD (KG)	MAX LOAD (lbs)	MAX PRESSURE (KPa)	MAX PRESSURE (PSI)	UTQG
	16 inch									
	205/55ZRF16	91W	6½J	214	632	615	1356	300	44	480 A A
	17 inch									
	205/55ZRF17	91W	6½J	214	658	615	1356	300	44	480 A A
	225/45ZRF17	94W XL	7½J	225	634	670	1477	340	50	480 A A
	225/50ZRF17	94W	7J	233	658	670	1477	300	44	480 A A
	225/55ZRF17	97W	7J	233	680	730	1609	300	44	480 A A
	18 inch									
NEW	225/40ZRF18	92Y XL	8J	230	637	630	1389	340	50	480 A A
NEW	225/45ZRF18	95Y XL	7½J	225	659	690	1521	340	50	480 A A
NEW	225/50ZRF18	95W	7J	233	683	690	1521	300	44	480 A A
NEW	245/40ZRF18	97W XL	8½J	248	653	730	1609	340	50	480 A A
NEW	245/45ZRF18	100W XL	8J	243	677	800	1764	340	50	480 A A
NEW	245/50ZRF18	100W	7½J	253	703	800	1764	300	44	480 A A
NEW	255/55RF18	105V	8J	265	737	925	2039	300	44	480 A A
	19 inch									
NEW	235/55ZRF19	101W	7½J	245	741	825	1819	300	44	480 A A
NEW	245/40ZRF19	98Y XL	8½J	248	679	750	1653	340	50	480 A A
NEW	255/45ZRF19	104W XL	8½J	255	713	900	1984	340	50	480 A A
NEW	255/50ZRF19	103W	8J	265	739	875	1929	300	44	480 A A
NEW	275/35ZRF19	100Y XL	9½J	278	675	800	1764	340	50	480 A A
	20 inch									
NEW	245/40ZRF20	99Y XL	8½J	248	704	775	1709	340	50	480 A A
NEW	245/45ZRF20	103W XL	8J	243	728	875	1929	340	50	480 A A
NEW	275/35ZRF20	102Y XL	9½J	278	700	850	1874	340	50	480 A A
NEW	275/40ZRF20	106W XL	9½J	278	728	950	2094	340	50	480 A A



No more delays or being stranded on remote highways due to a flat tire.



Helps to avoid accidents caused by the loss of control from punctures or air leaks, increasing



AC718

	TIRE SIZE	LOAD INDEX/ SPEED SYMBOL	STD. RIM (inch)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD (KG)	MAX LOAD (lbs)	MAX PRESSURE (KPa)	MAX PRESSURE (PSI)	UTQG
	17 inch									
	205/50ZR17	93W XL	6½J	214	638	650	1433	340	50	480 A A
	215/45ZR17	91W XL	7J	213	626	615	1356	340	50	480 A A
	215/50ZR17	95W XL	7J	226	648	690	1521	340	50	480 A A
	215/55ZR17	98W XL	7J	226	668	750	1653	340	50	480 A A
	225/45ZR17	94W XL	7½J	225	634	670	1477	340	50	480 A A
	225/45ZR17	94Y XL	7½J	225	634	670	1477	340	50	480 A A
	225/50ZR17	98W XL	7J	233	658	750	1653	340	50	480 A A
	225/55ZR17	101W XL	7J	233	680	825	1819	340	50	480 A A
NEW	235/50ZR17	100W XL	7½J	245	668	800	1764	340	50	480 A A
	235/55ZR17	103W XL	7½J	245	690	875	1929	340	50	480 A A
	18 inch									
	225/45ZR18	95W XL	7½J	225	659	690	1521	340	50	480 A A
NEW	225/50ZR18	95W	7J	233	683	690	1521	300	44	480 A A
	235/45ZR18	98W XL	8J	236	669	750	1653	340	50	480 A A
NEW	235/50ZR18	101W XL	7½J	245	693	825	1819	340	50	480 A A
NEW	245/40ZR18	97W XL	8½J	248	653	730	1609	340	50	480 A A
NEW	245/45ZR18	100W XL	8J	243	677	800	1764	340	50	480 A A
	19 inch									
NEW	235/50ZR19	103W XL	7½J	245	719	875	1929	340	50	480 A A
NEW	245/45ZR19	102W XL	8J	243	703	850	1874	340	50	480 A A
	20 inch									
NEW	235/50R20	104V XL	7½J	245	744	900	1984	340	50	480 A A



Simple yet effective pattern design improves grip and drainage capabilities which lower the risk of hydroplaning




Optimized tread formula ensures high traction and low rolling resistance on dry roads; hydroplaning resistance is improved



ULTRA HIGH PERFOR MANCE




AC 818



Asymmetric tread design with tiny internal pattern for better road grip and external big block for maximizing ground contact.

TIRE SIZE	LOAD INDEX/ SPEED SYMBOL	STD. RIM (inch)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD (KG)	MAX LOAD (lbs)	MAX PRESSURE (KPa)	MAX PRESSURE (PSI)	UTQG
16 inch									
185/50R16	81 V	6J	194	592	462	1019	300	44	480 A A
195/45R16	84 V XL	6½J	195	582	500	1102	340	50	480 A A
205/45ZR16	87 W XL	7J	206	590	545	1201	340	50	480 A A
215/45ZR16	90 W XL	7J	213	600	600	1323	340	50	480 A A
225/50ZR16	96 W XL	7J	233	632	710	1565	340	50	480 A A
17 inch									
205/40ZR17	84 W XL	7½J	212	596	500	1102	340	50	480 A A
205/45ZR17	88 W XL	7J	206	616	560	1235	340	50	480 A A
205/50ZR17	93 W XL	6½J	214	638	650	1433	340	50	480 A A
205/55ZR17	95 W XL	6½J	214	658	690	1521	340	50	480 A A
215/40ZR17	87 W XL	7½J	218	604	545	1201	340	50	480 A A
215/45ZR17	91 W XL	7J	213	626	615	1356	340	50	480 A A
215/50ZR17	95 W XL	7J	226	648	690	1521	340	50	480 A A
215/55ZR17	94 W	7J	226	668	670	1477	300	44	480 A A
215/55ZR17	98 W XL	7J	226	668	750	1653	340	50	480 A A
225/45ZR17	94 W XL	7½J	225	634	670	1477	340	50	480 A A
225/45ZR17	94 Y XL	7½J	225	634	670	1477	340	50	480 A A
225/50ZR17	98 W XL	7J	233	658	750	1653	340	50	480 A A
225/55ZR17	101 W XL	7J	233	680	825	1819	340	50	480 A A
235/45ZR17	97 W XL	8J	236	644	730	1609	340	50	480 A A
235/50R17	100 W XL	7½J	245	668	800	1764	340	50	480 A A
235/55ZR17	103 W XL	7½J	245	690	875	1929	340	50	480 A A
245/40ZR17	95 W XL	8½J	248	628	690	1521	340	50	480 A A
245/45ZR17	99 W XL	8J	243	652	775	1709	340	50	480 A A
20 inch									
235/45ZR20	100 W XL	8J	236	720	800	1764	340	50	480 A A
245/30ZR20	95 W XL	8½J	248	656	690	1521	340	50	480 A A
245/40ZR20	99 Y XL	8½J	248	704	775	1709	340	50	480 A A
255/35ZR20	97 Y XL	9J	260	686	730	1609	340	50	480 A A
255/40ZR20	101 Y XL	9J	260	712	825	1819	340	50	480 A A
265/40ZR20	104 Y XL	9½J	271	720	900	1984	340	50	480 A A
275/35ZR20	102 Y XL	9½J	278	700	850	1874	340	50	480 A A
21 inch									
245/35ZR21	96 Y XL	8½J	248	705	710	1565	340	50	480 A A
275/30ZR21	98 Y XL	9½J	278	699	750	1653	340	50	480 A A
275/35ZR21	103 Y XL	9½J	278	725	875	1929	340	50	480 A A
295/35ZR21	107 Y XL	10½J	301	739	975	2149	340	50	480 A A
295/40ZR21	111 Y XL	10½J	301	769	1090	2403	340	50	480 A A

TIRE SIZE	LOAD INDEX/ SPEED SYMBOL	STD. RIM (inch)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD (KG)	MAX LOAD (lbs)	MAX PRESSURE (KPa)	MAX PRESSURE (PSI)	UTQG
18 inch									
215/35ZR18	84 W XL	7½J	218	607	500	1102	340	50	480 A A
215/45ZR18	93W XL	7J	213	651	650	1433	340	50	480 A A
225/40ZR18	92 W XL	8J	230	637	630	1389	340	50	480 A A
225/40ZR18	92 Y XL	8J	230	637	630	1389	340	50	480 A A
225/45ZR18	95 W XL	7½J	225	659	690	1521	340	50	480 A A
225/50ZR18	95 W	7J	233	683	690	1521	300	44	480 A A
235/40ZR18	95 W XL	8½J	241	645	690	1521	340	50	480 A A
235/45ZR18	94 W	8J	236	669	670	1477	350	51	480 A A
235/45ZR18	98 W XL	8J	236	669	750	1653	340	50	480 A A
235/45ZR18	98 Y XL	8J	236	669	750	1653	340	50	480 A A
235/50ZR18	97 W	7½J	245	693	730	1609	350	51	480 A A
235/50ZR18	101W XL	7½J	245	693	825	1819	340	50	480 A A
245/40ZR18	97 W XL	8½J	248	653	730	1609	340	50	480 A A
245/45ZR18	100W XL	8J	243	677	800	1764	340	50	480 A A
245/50ZR18	104W XL	7½J	253	703	900	1984	340	50	480 A A
255/45ZR18	103W XL	8½J	255	687	875	1929	340	50	480 A A
255/40ZR18	99 Y XL	9J	260	661	775	1709	340	50	480 A A
265/35ZR18	97 Y XL	9½J	271	643	730	1609	340	50	480 A A
19 inch									
225/35ZR19	88W XL	8J	230	641	560	1235	340	50	480 A A
225/40ZR19	93W XL	8J	230	663	650	1433	340	50	480 A A
225/45ZR19	96W XL	7½J	225	685	710	1565	340	50	480 A A
225/55R19	103V XL	7J	233	731	875	1929	340	50	480 A A
235/35ZR19	91W XL	8½J	241	647	615	1356	340	50	480 A A
235/40ZR19	96Y XL	8½J	241	671	710	1565	340	50	480 A A
235/50ZR19	103W XL	7½J	245	719	875	1929	340	50	480 A A
245/35ZR19	93W XL	8½J	248	655	650	1433	340	50	480 A A
245/40ZR19	98W XL	8½J	248	679	750	1653	340	50	480 A A
245/45ZR19	102W XL	8J	243	703	850	1874	340	50	480 A A
255/35ZR19	96Y XL	9J	260	661	710	1565	340	50	480 A A
255/40ZR19	100Y/W XL	9J	260	687	800	1764	340	50	480 A A
255/45ZR19	104Y/W XL	8½J	255	713	900	1984	340	50	480 A A
265/30ZR19	93W XL	9½J	271	643	650	1433	340	50	480 A A
275/30ZR19	96W XL	9½J	278	649	710	1565	340	50	480 A A
275/35ZR19	100Y/W XL	9½J	278	675	800	1764	340	50	480 A A
275/40ZR19	105Y XL	9½J	278	703	925	2039	340	50	480 A A
20 inch									
245/30ZR20	90W XL	8½J	248	656	600	1323	340	50	480 A A
245/35ZR20	95 W XL	8½J	248	680	690	1521	340	50	480 A A
245/45ZR20	103Y XL	8J	243	728	875	1929	340	50	480 A A
22 inch									
275/40ZR22	107 Y XL	9½J	278	779	975	2149	340	50	480 A A
295/25ZR22	97 W XL	10½J	301	707	730	1609	340	50	480A A



Special tread design brings greater lateral rigidity and longitudinal flexibility



The optimal distribution of the tread pattern blocks and grooves achieves optimum balance of control, giving low noise and driving comfort.



Long mileage and driving comfort



AC 828

TIRE SIZE	LOAD INDEX/ SPEED SYMBOL	STD. RIM (inch)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD (KG)	MAX LOAD (lbs)	MAX PRESSURE (KPa)	MAX PRESSURE (PSI)	UTQG
15 inch									
205/75R15 (WSW)	97 H	5½J	203	689	730	1609	300	44	520 A A
205/75R15	97 H	5½J	203	689	730	1609	300	44	520 A A
215/75R15 (WSW)	100 H	6J	216	703	800	1764	300	44	520 A A
215/75R15 (WL)	100 H	6J	216	703	800	1764	300	44	520 A A
215/75R15	100 H	6J	216	703	800	1764	300	44	520 A A
225/70R15	100 H	6½J	228	697	800	1764	300	44	520 A A
225/70R15 (WSW)	100 H	6½J	228	697	800	1764	300	44	520 A A
225/75R15 (WSW)	102 H	6J	223	719	850	1874	300	44	520 A A
225/75R15	102 H	6J	223	719	850	1874	300	44	520 A A
225/75R15 (WL)	102 H	6J	223	719	850	1874	300	44	520 A A
235/75R15	105 H	6½J	235	733	925	2039	300	44	520 A A
235/75R15 (WSW)	105 H	6½J	235	733	925	2039	300	44	520 A A
255/70R15	108 H	7½J	260	739	1000	2205	350	51	520 A A
265/70R15	112 H	8J	272	753	1120	2469	350	51	520 A A
16 inch									
205/65R16	95 H	6J	209	672	690	1521	300	44	520 A A
215/65R16	98 H	6½J	221	686	750	1653	300	44	520 A A
215/70R16	100 H	6½J	221	708	800	1764	350	51	520 A A
225/70R16	103 H	6½J	228	722	875	1929	350	51	520 A A
235/60R16	100 H	7J	240	688	800	1764	300	44	520 A A
235/65R16	103 H	7J	240	712	875	1929	300	44	520 A A
235/70R16	106 H	7J	240	736	950	2094	350	51	520 A A
245/70R16	107 H	7J	248	750	975	2149	350	51	520 A A
245/70R16	111 H XL	7J	248	750	1090	2403	340	50	520 A A
245/75R16	111 H	7J	248	774	1090	2403	350	51	520 A A
255/65R16	109 H	7½J	260	738	1030	2271	300	44	520 A A
255/70R16	111 H	7½J	260	764	1090	2403	350	51	520 A A
265/70R16	112 H	8J	272	778	1120	2469	350	51	520 A A
265/70R16	115 H XL	8J	272	778	1215	2679	340	50	520 A A
265/75R16	116 H	7½J	267	804	1250	2756	350	51	520 A A
275/70R16	114 H	8J	279	792	1180	2601	350	51	520 A A
20 inch									
235/55R20	105 V XL	7½J	245	766	925	2039	340	50	520 A A
245/50R20	102 V	7½J	253	754	850	1874	350	51	520 A A
255/45ZR20	105 W XL	8½J	255	738	925	2039	340	50	520 A A
255/50R20	109 V XL	8J	265	764	1030	2271	340	50	520 A A
255/55R20	110 V XL	8J	265	788	1060	2337	340	50	520 A A
NEW 265/50R20	111 V XL	8½J	277	774	1090	2403	340	50	520 A A
NEW 265/55R20	113 V XL	8½J	277	800	1150	2535	340	50	520 A A
275/40ZR20	106 Y XL	9½J	278	728	950	2094	340	50	520 A A
275/45ZR20	110 Y XL	9J	273	756	1060	2337	340	50	520 A A
275/50ZR20	113 W XL	8½J	284	784	1150	2535	340	50	520 A A
NEW 275/55R20	117 V XL	8½J	284	810	1285	2833	340	50	520 A A
275/60R20	115 H	8J	279	838	1215	2679	300	44	520 A A
285/45ZR20	112 W XL	9½J	285	764	1120	2469	340	50	520 A A
285/50R20	116 V XL	9J	297	794	1250	2756	340	50	520 A A
NEW 315/35ZR20	110 Y XL	11J	320	728	1060	2337	340	50	520 A A
21 inch									
275/45ZR21	110 Y XL	9J	273	781	1060	2337	340	50	520 A A
275/50ZR21	113 W XL	8½J	284	809	1150	2535	340	50	520 A A
NEW 315/40ZR21	115 Y XL	11J	320	785	1215	2679	340	50	520 A A
22 inch									
NEW 285/45R22	114 V XL	9½J	285	815	1180	2601	340	50	520 A A
NEW 295/40ZR22	112 Y XL	10½J	301	795	1120	2469	340	50	520 A A



SUV

TIRE SIZE	LOAD INDEX/ SPEED SYMBOL	STD. RIM (inch)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD (KG)	MAX LOAD (lbs)	MAX PRESSURE (KPa)	MAX PRESSURE (PSI)	UTQG
17 inch									
215/60R17	96 H	6½J	221	690	710	1565	300	44	520 A A
215/65R17	99 H	6½J	221	712	775	1709	300	44	520 A A
225/60R17	99 H	6½J	228	702	775	1709	300	44	520 A A
225/65R17	102 H	6½J	228	724	850	1874	300	44	520 A A
225/70R17	108H XL	6½J	228	748	1000	2205	340	50	520 A A
235/60R17	102 H	7J	240	714	850	1874	300	44	520 A A
235/65R17	104 H	7J	240	738	900	1984	350	51	520 A A
235/70R17	109H XL	7J	240	762	1030	2271	340	50	520 A A
245/65R17	107 H	7J	248	750	975	2149	350	51	520 A A
245/70R17	110 H	7J	248	776	1060	2337	350	51	520 A A
255/60R17	106 H	7½J	260	738	950	2094	350	51	520 A A
255/65R17	110 H	7½J	260	764	1060	2337	350	51	520 A A
265/65R17	112 H	8J	272	776	1120	2469	350	51	520 A A
265/70R17	115 H	8J	272	804	1215	2679	350	51	520 A A
NEW 275/65R17	115 H	8J	279	790	1215	2679	300	44	520 A A
18 inch									
215/50ZR18	92 W	7J	226	673	630	1389	300	44	520 A A
215/55R18	99W XL	7J	226	693	775	1709	340	50	520 A A
225/55R18	102W XL	7J	233	705	850	1874	340	50	520 A A
225/60R18	100 H	6½J	228	727	800	1764	300	44	520 A A
225/60R18	100 V	6½J	228	727	800	1764	300	44	520 A A
235/55R18	104W XL	7½J	245	715	900	1984	340	50	520 A A
235/60R18	107 H XL	7J	240	739	975	2149	340	50	520 A A
235/60R18	107 V XL	7J	240	739	975	2149	340	50	520 A A
235/65R18	110 H XL	7J	240	763	1060	2337	340	50	520 A A
245/60R18	105 H	7J	248	751	925	2039	350	51	520 A A
255/55R18	109 V XL	8J	265	737	1030	2271	340	50	520 A A
255/55R18	109W XL	8J	265	737	1030	2271	340	50	520 A A
255/60R18	112 H XL	7½J	260	763	1120	2469	340	50	520 A A
255/60R18	112 V XL	7½J	260	763	1120	2469	340	50	520 A A
255/70R18	113 H	7½J	260	815	1150	2535	300	44	520 A A
NEW 265/60R18	110 H	8J	272	775	1060	2337	350	51	520 A A
NEW 265/65R18	114 H	8J	272	801	1180	2601	300	44	520 A A
265/70R18	116 H	8J	272	829	1250	2756	300	44	520 A A
NEW 275/65R18	116 H	8J	279	815	1250	2756	300	44	520 A A
285/60R18	116 H	8½J	292	799	1250	2756	300	44	520 A A
19 inch									
235/45ZR19	99 W XL	8J	236	695	775	1709	340	50	520 A A
235/55R19	105 V XL	7½J	245	741	925	2039	340	50	520 A A
245/50ZR19	105 W XL	7½J	253	729	925	2039	340	50	520 A A
245/55R19	103 V	7½J	253	753	875	1929	350	51	520 A A
255/50R19	107W XL	8J	265	739	975	2149	340	50	520 A A
255/50R19	107 Y XL	8J	265	739	975	2149	340	50	520 A A
255/55R19	111 V XL	8J	265	763	1090	2403	340	50	520 A A
255/60R19	109 H	7½J	260	789	1030	2271	300	44	520 A A
265/50R19	110W XL	8½J	277	749	1060	2337	340	50	520 A A



Unique carbon polymer composite efficiently improve the traction capability and reduces the rolling resistance.



Optimized pitch arrangement and tread profile reduces noise



High density longitudinal and lateral zigzag pattern design ensures close connection between tire tread and road surface to increase lateral rigidity



Four longitudinal grooves and a wide contact area provide outstand drainage performance and manoeuvrability




WINTER TYRE

TIRE SIZE	LOAD INDEX/ SPEED SYMBOL	STD. RIM (inch)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD (KG)	MAX LOAD (lbs)	MAX PRESSURE (KPa)	MAX PRESSURE (PSI)
13 inch								
175/70R13	82 T	5.00B	177	576	475	1047	300	44
14 inch								
155/65R14	75 T	4½J	157	558	387	853	300	44
165/70R14	81 T	5J	170	588	462	1019	300	44
175/65R14	82 T	5J	177	584	475	1047	300	44
185/60R14	82 T	5½J	189	578	475	1047	300	44
185/65R14	86 T	5½J	189	596	530	1168	300	44
15 inch								
175/65R15	84 T	5J	177	609	500	1102	300	44
185/55R15	86 H XL	6J	194	585	530	1168	340	50
185/60R15	84 T	5½J	189	603	500	1102	300	44
185/65R15	88 T	5½J	189	621	560	1235	300	44
195/50R15	86 H XL	6J	201	577	530	1168	340	50
195/55R15	85 H	6J	201	595	515	1135	300	44
195/60R15	88 H	6J	201	615	560	1235	300	44
195/65R15	91 T	6J	201	635	615	1356	300	44
205/65R15	94 H	6J	209	647	670	1477	300	44
195/70R15C	8PR 104/102 R	6J	201	655	900/850	1985/1875	450	65
215/70R15C	8PR 109/107 R	6½J	221	683	1030/975	2270/2150	450	65
225/70R15C	8PR 112/110 R	6½J	228	697	1120/1060	2470/2335	450	65
16 inch								
195/55R16	91H XL	6J	201	620	615	1356	340	50
205/55R16	91 H	6½J	214	632	615	1356	300	44
205/60R16	92 H	6J	209	652	630	1389	300	44
215/55R16	97 H XL	7J	226	642	730	1609	340	50
215/60R16	99 H XL	6½J	221	664	775	1709	340	50
215/65R16	98 H	6½J	221	686	750	1653	300	44
195/65R16C	8PR 104/102 R	6J	201	660	900/850	1985/1875	475	69
195/75R16C	8PR 107/105 R	5½J	196	698	975/925	2150/2040	475	69
205/65R16C	8PR 107/105 R	6J	209	672	975/925	2150/2040	475	69
215/65R16C	8PR 109/107 R	6½J	221	686	1030/975	2270/2150	475	69
235/65R16C	8PR 115/113 R	7J	240	712	1215/1150	2680/2535	475	69
17 inch								
205/50R17	93 H XL	6½J	214	638	650	1433	340	50
225/45R17	94 H XL	7½J	225	634	670	1477	340	50
225/50R17	98 H XL	7J	233	658	750	1653	340	50
225/55R17	101 H XL	7J	233	680	825	1819	340	50



ARCTIC W6



Premium studless winter tyre providing excellent snow, slush and wet traction in cold climates

Special pattern design to promote aggressive bite in deep snow and wet road conditions

Superior tread compound keeps rubber flexible for maximum performance in extreme cold temperatures in winter

TIRE SIZE	LOAD INDEX/ SPEED SYMBOL	STD. RIM (inch)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD (KG)	MAX LOAD (lbs)	MAX PRESSURE (KPa)	MAX PRESSURE (PSI)
13 inch								
165/70R13	79 T	5.00B	170	562	437	963	300	44
14 inch								
175/70R14	84 T	5J	177	602	500	1102	300	44
185/70R14	88 T	5½J	189	616	560	1235	300	44
195/60R14	86 T	6J	201	590	530	1168	300	44
175R14LT	8PR 99/97 R	5J	177	636	775/730	1710/1610	450	65
185R14LT	8PR 102/100R	5½J	189	652	850/800	1875/1765	450	65
15 inch								
195/60R15	88 T	6J	201	615	560	1235	300	44
195/65R15	91 T	6J	201	635	615	1356	300	44
205/70R15	96 S	6J	209	669	710	1565	300	44
215/75R15	100S	6J	216	703	800	1764	300	44
235/75R15	105S	6½J	235	733	925	2039	350	51
16 inch								
195/60R16	89 T	6J	201	640	580	1279	300	44
205/55R16	91 H	6½J	214	632	615	1356	300	44
215/70R16	100 S	6½J	221	708	800	1764	350	51
235/70R16	106 S	7J	240	736	950	2094	350	51
17 inch								
225/45R17	94 H XL	7½J	225	634	670	1477	340	50



AC 868



Four longitudinal grooves improve draining performance and grip capacity on snow



Asymmetric tread design improves cornering manoeuvrability.



High density and uniform distribution on silica nanoparticles provides a silent ride with the best ride comfort.



WINTER TYRE



arctic w-8



Asymmetric pattern design provides superior handing on snow surface

Optimised lateral groove angle offers strong snow performance

	TIRE SIZE	LOAD INDEX/ SPEED SYMBOL	STD. RIM (inch)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD (KG)	MAX LOAD (lbs)	MAX PRESSURE (KPa)	MAX PRESSURE (PSI)
	13 inch								
NEW	155/65R13	73T	4.50B	157	532	365	805	300	44
	14 inch								
NEW	155/65R14	75T	4½J	157	558	387	853	300	44
	15 inch								
NEW	185/60R15	88H XL	5½J	189	603	560	1235	340	50
NEW	185/65R15	92T XL	5½J	189	621	630	1389	340	50
NEW	195/65R15	91T	6J	201	635	615	1356	300	44
	16 inch								
NEW	205/55R16	94 H XL	6½J	214	632	670	1477	340	50
NEW	205/60R16	96 H XL	6J	209	652	710	1565	340	50
NEW	205/65R16	95 T	6J	209	672	690	1521	300	44
NEW	215/55R16	97 H XL	7J	226	642	730	1609	340	50
NEW	215/60R16	99 H XL	6½J	221	664	775	1709	340	50
NEW	215/65R16	98 H	6½J	221	686	750	1653	300	44
NEW	225/60R16	98 T	6½J	228	676	750	1653	300	44
	17 inch								
NEW	205/50R17	93 H XL	6½J	214	638	650	1433	340	50
NEW	205/55R17	91 H	6½J	214	658	615	1356	300	44
	215/45R17	91 H XL	7J	213	626	615	1356	340	50
	215/50R17	95 H XL	7J	226	648	690	1521	340	50
	215/55R17	98 T XL	7J	226	668	750	1653	340	50
NEW	225/45R17	94 H XL	7½J	225	634	670	1477	340	50
NEW	225/50R17	98 H XL	7J	233	658	750	1653	340	50
NEW	225/55R17	101 H XL	7J	233	680	825	1819	340	50
NEW	235/45R17	97 H XL	8J	236	644	730	1609	340	50
	235/55R17	99 S	7½J	245	690	775	1709	300	44
	18 inch								
NEW	225/40R18	92 H XL	8J	230	637	630	1389	340	50
	225/45R18	95 S XL	7½J	225	659	690	1521	340	50
	225/50R18	99 T XL	7J	233	683	775	1709	340	50
	235/45R18	98 S XL	8J	236	669	750	1653	340	50
NEW	245/40R18	97 V XL	8½J	248	653	730	1609	340	50
	245/45R18	96 S	8J	243	677	710	1565	300	44
NEW	255/40R18	99 V XL	9J	260	661	775	1709	340	50
	19 inch								
NEW	235/40R19	96 H XL	8½J	241	671	710	1565	340	50
NEW	245/40R19	98 V XL	8½J	248	679	750	1653	340	50
NEW	245/45R19	102 V XL	8J	243	703	850	1874	340	50
	255/40R19	100 T XL	9J	260	687	800	1764	340	50
	275/35R19	100 V XL	9½J	278	675	800	1764	340	50
	20 inch								
NEW	255/40R20	101 V XL	9J	260	712	825	1819	340	50
	255/50R20	109 S XL	8J	265	764	1030	2271	340	50



WINTER TYRE



ARCTIC W-9



New studless winter tyres for SUV/CUV vehicles promise excellent performance on snow and wet road surface

SILICA TECH compound offers remarkable traction and longer tread life

	TIRE SIZE	LOAD INDEX/ SPEED SYMBOL	STD. RIM (inch)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD (KG)	MAX LOAD (lbs)	MAX PRESSURE (KPa)	MAX PRESSURE (PSI)
	15 inch								
NEW	195/70R15C 8PR	104/102R	6J	201	655	900/850	1985/1875	450	65
	16 inch								
NEW	245/70R16	107 T	7J	248	750	975	2149	300	44
	215/75R16LT 8PR	107/103R	6J	216	728	975/875	2150/1930	450	65
	265/70R16	112 T	8J	272	778	1120	2469	300	44
	17 inch								
	215/60R17	96 S	6½J	221	690	710	1565	300	44
	225/60R17	99 S	6½J	228	702	775	1709	300	44
	225/65R17	102 S	6½J	228	724	850	1874	300	44
	235/65R17	104 T	7J	240	738	900	1984	300	44
	265/65R17	112 S	8J	272	776	1120	2469	300	44
NEW	245/70R17LT 8PR	114/110R	7J	248	776	1180/1060	2600/2335	450	65
	18 inch								
NEW	215/50R18	92 V	7J	226	673	630	1389	300	44
	215/55R18	99 H XL	7J	226	693	775	1709	340	50
	225/55R18	98 T	7J	233	705	750	1653	300	44
	225/60R18	100 S	6½J	228	727	800	1764	300	44
	235/50R18	101 T XL	7½J	245	693	825	1819	340	50
	235/55R18	100 T	7½J	245	715	800	1764	300	44
	235/60R18	107 S XL	7J	240	739	975	2149	340	50
NEW	235/65R18	110 T XL	7J	240	763	1060	2337	340	50
	245/60R18	105 T	7J	248	751	925	2039	300	44
NEW	265/60R18	110 H	8J	272	775	1060	2337	300	44
	285/60R18	116 R	8½J	292	799	1250	2756	300	44

	19 inch								
	225/45R19	96 T XL	7½J	225	685	710	1565	340	50
NEW	225/55R19	103 H XL	7J	233	731	875	1929	340	50
NEW	235/50R19	103 H XL	7½J	245	719	875	1929	340	50
	235/55R19	105 T XL	7½J	245	741	925	2039	340	50
	245/55R19	103 T	7½J	253	753	875	1929	300	44
NEW	255/45R19	104 V XL	8½J	255	713	900	1984	340	50
NEW	255/55R19	111 H XL	8J	265	763	1090	2403	340	50
NEW	255/55R19	111 V XL	8J	265	763	1090	2403	340	50
NEW	265/55R19	109 H	8½J	277	775	1030	2271	300	44
	20 inch								
NEW	235/50R20	104 H XL	7½J	245	744	900	1984	340	50
NEW	235/55R20	105 H XL	7½J	245	766	925	2039	340	50
NEW	245/45R20	103 V XL	8J	243	728	875	1929	340	50
NEW	245/50R20	102 T	7½J	253	754	850	1874	300	44
NEW	255/45R20	105 V XL	8½J	255	738	925	2039	340	50
NEW	255/55R20	110 H XL	8J	265	788	1060	2337	340	50
	285/50R20	112 S	9J	297	794	1120	2469	300	44
	21 inch								
NEW	265/45R21	104 H	9J	266	771	900	1984	300	44



LIGHT TRUCK



AC 838

TIRE SIZE	LOAD INDEX/ SPEED SYMBOL	STD. RIM (inch)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD (KG)	MAX LOAD (lbs)	MAX PRESSURE (KPa)	MAX PRESSURE (PSI)
12 inch								
145/80R12LT	6PR 80/78N	4.00B	145	537	450/425	992/937	350	50
13 inch								
155R13C	8PR 90/88Q	4.50B	157	578	600/560	1323/1235	450	65
165R13C	8PR 94/93S	4.50B	167	596	670/650	1477/1433	450	65
14 inch								
165/14C	8PR 97/95S	4½J	167	622	730/690	1609/1521	450	65
175R14C	8PR 99/97 R	5J	177	636	775/730	1710/1610	450	65
185R14C	8PR 102/100R	5½J	188	650	850/800	1875/1765	450	65
185R14C	6PR 97/95 R	5½J	188	650	730/690	1610/1520	350	51
195R14C	8PR 106/104R	5½J	198	666	950/900	2095/1985	450	65
195R14C(WSW)	8PR 106/104R	5½J	198	666	950/900	2095/1985	450	65
15 inch								
195R15C	8PR 106/104R	5½J	198	690	950/900	2095/1985	450	65
195R15C (WSW)	8PR 106/104R	5½J	198	690	950/900	2095/1985	450	65
195/70R15C	8PR 104/102R	6J	201	655	900/850	1985/1875	450	65
205/70R15C	8PR 106/104R	6J	209	669	950/900	2095/1985	450	65
215R15C	8PR 111/109R	6J	218	724	1090/1030	2405/2270	450	65
215/65R15C	6PR 104/102T	6½J	221	661	900/850	1985/1875	375	55
215/70R15C	8PR 109/107R	6½J	221	683	1030/975	2270/2150	450	65
225/70R15C	8PR 112/110R	6½J	228	697	1120/1060	2470/2335	450	65
225/70R15C (WSW)	8PR 112/110R	6½J	228	697	1120/1060	2470/2335	450	65

	TIRE SIZE	LOAD INDEX/ SPEED SYMBOL	STD. RIM (inch)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD (KG)	MAX LOAD (lbs)	MAX PRESSURE (KPa)	MAX PRESSURE (PSI)
16 inch									
	185/75R16C	8PR 104/102R	5J	184	684	900/850	1985/1875	475	69
NEW	185/85R16C	12PR 111/109 N	5J	184	720	1090/1030	2405/2270	650	95
	195/60R16C	6PR 99/97 T	6J	201	640	775/730	1710/1610	375	55
	195/65R16C	8PR 104/102T	6J	201	660	900/850	1985/1875	475	69
	195/75R16C	8PR 107/105R	5½J	196	698	975/925	2150/2040	475	69
NEW	195/85R16C	12PR 114/112 N	5½J	196	738	1180/1120	2600/2470	650	95
	205/65R16C	8PR 107/105T	6J	209	672	975/925	2150/2040	475	69
	205/75R16C	8PR 110/108R	5½J	203	714	1060/1000	2335/2205	475	69
NEW	205/85R16C	12PR 117/115 N	5½J	203	754	1285/1215	2835/2680	650	95
	215/60R16C	6PR 103/101T	6½J	221	664	875/825	1930/1820	375	55
	215/60R16C	8PR 108/106T	6½J	221	664	1000/950	2205/2095	475	69
	215/65R16C	8PR 109/107T	6½J	221	686	1030/975	2270/2150	475	69
	215/70R16C	6PR 108/106R	6½J	221	708	1000/950	2205/2095	375	55
	215/75R16C	8PR 113/111R	6J	216	728	1150/1090	2535/2405	475	69
	225/65R16C	8PR 112/110T	6½J	228	698	1120/1060	2470/2335	475	69
	235/65R16C	8PR 115/113T	7J	240	712	1215/1150	2680/2535	475	69

AC 838



Closed shoulder design provides superior lateral rigidity, traction and braking capacity



zigzag design provides excellent grip.



LIGHT TRUCK



AC 858

TIRE SIZE	LOAD INDEX/ SPEED SYMBOL	STD. RIM (inch)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD (KG)	MAX LOAD (lbs)	MAX PRESSURE (KPa)	MAX PRESSURE (PSI)	UTQG
15 inch									
LT215/75R15	6PR 100/97 S	6J	216	703	800/730	1765/1610	350	5 1	
LT225/75R15	6PR 102/99 S	6J	223	719	850/775	1875/1710	350	5 1	
LT235/75R15	6PR 104/101R	6½J	235	733	900/825	1985/1820	350	50	
LT235/75R15	8PR 110/107S	6½J	235	733	1060/975	2335/2150	450	65	
31X10.50R15LT	6PR 109 R	8½J	268	775	1030	2270	350	50	
16 inch									
205/80R16	104 S XL	5½J	203	734	900	1984	340	50	520 A A
205R16C	8PR 110/108R	6J	208	736	1060/1000	2337/2205	450	65	
LT215/85R16	10PR 115/112R	6J	216	772	1215/1120	2680/2470	550	80	
LT225/75R16	10PR 115/112R	6J	223	744	1215/1120	2680/2470	550	80	
235/70R16	106 T	7J	240	736	950	2094	350	51	520 A A
LT235/85R16	10PR 120/116R	6½J	235	806	1380/1260	3042/2778	550	80	
245/70R16	107 T	7J	248	750	975	2149	350	51	520 A A
245/70R16	111 T XL	7J	248	750	1090	2403	340	50	520 A A
LT245/75R16	10PR 120/116R	7J	248	774	1380/1260	3042/2778	550	80	
NEW LT245/85R16	10PR 121/118Q	7J	248	822	1450/1320	3195/2910	550	80	
265/70R16	112 T	8J	272	778	1120	2469	350	51	520 A A
LT265/75R16	10PR 120/117R	7½J	267	804	1400/1285	3085/2835	550	80	
LT265/75R16	10PR 123/120R	7½J	267	804	1550/1400	3415/3085	550	80	
NEW LT285/75R16	10PR 121/118Q	8J	286	834	1450/1320	3195/2910	550	80	
17 inch									
265/65R17	112 T	8J	272	776	1120	2469	350	51	520 A A
265/70R17	115 T	8J	272	804	1215	2679	350	51	520 A A
NEW LT285/70R17	10PR 121/118Q	8½J	292	832	1450/1320	3195/2910	550	80	
18 inch									
265/60R18	110 T	8J	272	775	1060	2337	350	51	520 A A
20 inch									
265/50R20	111 T XL	8½J	277	774	1090	2403	340	50	520 A A



Strong carcass and convex sidewall design ensures superior wear resistance



Wide open shoulder design provides superior lateral rigidit traction and braking capacity

TIRE SIZE	LOAD INDEX/ SPEED SYMBOL	STD. RIM (inch)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD (KG)	MAX LOAD (lbs)	MAX PRESSURE (KPa)	MAX PRESSURE (PSI)
15 inch								
31X10.50R15LT	6PR 109Q	8½J	268	775	1030	2270	350	50
32X11.50R15LT	6PR 113Q	9J	290	801	1150	2535	350	50
33X12.50R15LT	6PR 108Q	10J	318	826	1000	2205	250	35
35X12.50R15LT	6PR 113Q	10J	318	877	1150	2535	250	35
16 inch								
LT265/70R16	8PR 117/114Q	8J	272	778	1285/1180	2835/2600	450	65
LT265/75R16	8PR 119/116Q	7½J	267	804	1360/1250	3000/2755	450	65
LT265/75R16	10PR 123/120Q	7½J	267	804	1550/1400	3415/3085	550	80
LT285/75R16	6PR 116/113Q	8J	286	834	1250/1150	2755/2535	350	50
LT285/75R16	10PR 126/123Q	8J	286	834	1700/1550	3750/3415	550	80
LT305/70R16	8PR 118/115Q	9J	311	834	1320/1215	2910/2680	350	50
LT305/70R16	10PR 124/121Q	9J	311	834	1600/1450	3525/3195	450	65
LT315/75R16	8PR 121/118Q	8½J	313	878	1450/1320	3195/2910	350	50
LT315/75R16	10PR 127/124Q	8½J	313	878	1750/1600	3860/3525	450	65
17 inch								
LT265/70R17	10PR 121/118Q	8J	272	804	1450/1320	3195/2910	550	80
LT285/70R17	10PR 121/118Q	8½J	292	832	1450/1320	3195/2910	550	80



GRANDTRAC MT1



Optimized tread formula design provides ultra-strong traction performance and puncture resistance.



Shoulder Design Open shoulder design with dilated and deepened grooves allows for easier discharge of mud when driving at low or high speeds.






AC 898

TIRE SIZE	PR	LOAD INDEX/ SPEED SYMBOL	STD. RIM (inch)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD (KG)	(lbs)	MAX PRESSURE (KPa)	(PSI)
16 inch									
7.00R16LT	12PR	115/110N	5.50F	200	775	1215/1060	2680/2335	670	97
7.00R16LT	8PR	107/102 N	5.50F	200	775	975/850	2150/1875	460	67
7.00R16LT	6PR	101/96 N	5.50F	200	775	825/710	1820/1565	350	50
7.50R16LT	14PR	122/118N	6.00G	215	805	1500/1320	3305/2910	770	112
7.50R16LT	14PR	120/118N	6.00G	215	805	1400/1320	3085/2910	770	112



Optimized wet and dry performance, highly efficient in preventing side wear, and longer mileage.



Strengthened tire structure and reinforced carcass ensure greater load capacity.

NEW

TIRE SIZE	LOAD INDEX/ SPEED SYMBOL	STD. RIM (inch)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD (KG)	(lbs)	MAX PRESSURE (KPa)	(PSI)	UTQG
17 inch									
215/50ZR17	95 W XL	7J	226	648	690	1521	340	50	480 A A
215/55ZR17	98 W XL	7J	226	668	750	1653	340	50	520 A A
18 inch									
215/55ZR18	99 W XL	7J	226	693	775	1709	340	50	480 A A
235/45ZR18	98 Y XL	8J	236	669	750	1653	340	50	480 A A
245/50ZR18	104 W XL	7½J	253	703	900	1984	340	50	480 A A
19 inch									
245/45ZR19	102 Y XL	8J	243	703	850	1874	340	50	480 A A
20 inch									
255/50ZR20	109 W XL	8J	265	764	1030	2271	340	50	480 A A
21 inch									
265/45ZR21	108 Y XL	9J	266	771	1000	2205	340	50	480 A A



EPFOUNDER CE101



Silence and comfort from unique pattern design.

Safe driving on wet roads. Better wet grip through a new innovative tread compound.

Longer tread life through optimized profile for even wear.